


Features

- Low V_F schottky barrier rectifiers
- Low profile - typical height 1.0 mm
- Low forward voltage drop
- Low leakage current
- Moisture sensitivity: level 1, per J-STD-020
- AEC-Q101 qualified
- High temperature soldering guaranteed: 260°C/10 seconds
- Halogen-free according to IEC 61249-2-21 definition

Package: eSGA
(SOD-123FL)**Applications**

For use in fast switching in RF module, lighting, cell phone, portable devices, power supply and other consumer applications.

Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	FS12	FS13	FS14	FS16	FS1B	FS1B5H	FS1CH	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	60	100	150	200	V
Maximum RMS Voltage	V_{RMS}	14	21	28	42	70	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	30	40	60	100	150	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$				1.0				A
Peak Forward Surge Current (8.3 ms single half sine-wave superimposed on rated load)	I_{FSM}				30.0				A
Operation Junction Temperature Range	T_J				- 55 to + 150				$^\circ\text{C}$
Storage Temperature Range	T_{STG}				- 55 to + 150				$^\circ\text{C}$

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Test Conditions	Symbol	FS12	FS13	FS14	FS16	FS1B	FS1B5H	FS1CH	Unit
Maximum Instantaneous Forward Voltage	$I_F=0.5\text{A}, T_A=25^\circ\text{C}$	V_F	0.40	0.45		0.55	0.75	0.80		V
	$I_F=1\text{A}, T_A=25^\circ\text{C}$			0.50		0.70	0.81	0.90		
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_A=25^\circ\text{C}$	I_R	200	200		200	150	200		μA
	$T_A=125^\circ\text{C}$		10	30			20			mA
Typical Thermal Resistance ¹⁾	Junction to Ambient	$R_{\theta JA}$			90					$^\circ\text{C/W}$
	Junction to Case	$R_{\theta JC}$			60					
	Junction to Mount	$R_{\theta JM}$			20					

Note:1) The thermal resistance from junction to ambient, case or mount, mounted on P.C.B with 5x5mm copper pads, 2 OZ, FR4 PCB


Ratings and Characteristics Curves ($T_A = 25^\circ C$ unless otherwise noted)


Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Reverse Characteristics




Figure 4. Typical Junction Capacitance






Figure 5. Typical Instantaneous Forward Characteristics

Package Outline Dimensions

eSGA (SOD-123FL)


DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.9	1.08	0.035	0.043
A1	0	0.1	0.000	0.004
B	0.85	1.05	0.033	0.041
C	0.1	0.25	0.004	0.010
D	1.7	2	0.067	0.079
E	2.9	3.1	0.114	0.122
L	0.43	0.83	0.017	0.033
HE	3.5	3.9	0.138	0.154

Soldering footprint


Packing Information

Packing quantities

3000 pcs/Reel, 40 Reels/Box; 8mm Tape, 7" Reel

Tape & Reel Spec

