

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939

HER601 THRU HER608

Features

- **High Surge Current Capability**
- High Reliability
- Low Forward Voltage Drop Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information) Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- For capacitive load, derate current by 20%

MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
HER601	HER601	50V	35V	50V
HER602	HER602	100V	70V	100V
HER603	HER603	200V	140V	200V
HER604	HER604	300V	210V	300V
HER605	HER605	400V	280V	400V
HER606	HER606	600V	420V	600V
HER607	HER607	800V	560V	800V
HER608	HER608	1000V	700V	1000V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	6 A	T _A = 55°C
Peak Forward Surge Current	I _{FSM}	200A	8.3ms, half sine
Maximum			
Instantaneous			
Forward Voltage			
HER601-604 HER605 HER606-608	V_{F}	1.1V 1.3V 1.7V	$I_{FM} = 6.0A;$ $T_A = 25^{\circ}C$
Reverse Current At Rated DC Blocking Voltage (Maximum DC)	I _R	10μΑ 200μΑ	$T_A = 25$ °C $T_A = 100$ °C
Maximum Reverse			
Recovery Time			
HER601-605	T_{rr}	50ns	$I_F=0.5A, I_R=1.0A,$
HER606-608		75ns	I _{rr} =0.25A
Typical Junction			
Capacitance			
HER601-605	C_{J}	100pF	Measured at
HER606-608	-	65pF	1.0MHz, V _R =4.0V

1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

6.0 Amp High **Efficient Rectifiers** 50 to 1000 Volts

R-6



DIMENSIONS							
	INCHES		ММ				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.340	.360	8.60	9.10			
В	.340	.360	8.60	9.10			
O	.048	.052	1.20	1.30			
D	1.000		25.40				


www.mccsemi.com


HER601 thru HER608



RATINGS AND CHARACTERISTIC CURVES

FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM












FIG.3- TYPICAL REVERSE CHARACTERISTICS











Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 500pcs/Reel
Part Number-AP	Ammo Packing: 450pcs/Ammo Box
Part Number-BP	Bulk: 4.8Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.