Product Summary **ANN-MS series**

High performance active GPS antennas

Highlights

- High performance active GPS antenna
- Low noise figure and high gain coverage
- Fast and easy integration
- No antenna know-how necessary
- Magnetic base suitable for mounting on car roof
- Industrial temperature range: -40 ° C to +85 ° C

Product description

The high performance ANN-MS active GPS antenna with integrated low-noise amplifier (LNA) is the perfect match to u-blox GPS receivers where high sensitivity and optimum sky coverage are essential. ANN-MS offers the high performance to exploit the full capabilities of all u-blox GPS receivers, and can be operated at a supply voltage of 2.7 to 5.5 V.

Patch antenna characteristics

Frequency	1575 ± 3 MHz
VSWR	Max. 2.0
Bandwidth	Min. 20 MHz
Impedance	50 Ω
Peak gain	Min. 4 dBic (on 7 x 7 cm ground plane)
Gain coverage	≥ -4 dBic, at -90° ≤ θ ≤ +90° (over 75% volume)
Polarization	RHCP (right-handed circular polarization)

Amplifier characteristics

Gain without cable	Typ. 29 dB
Noise figure	Max. 0.9 dB
Output VWSR	Max. 2.0
DC voltage	2.7 V – 5.5 V
DC current	Typ 8.5 mA, ± 4.5 mA



48 x 40 x 13 mm, 5 m coaxial cable

Mechanical data

Weight	42 g (without cable)
Size	48 x 40 x 13 mm
Cable	5 m RG174 standard
Connectors (choice)	SMA, SMB, MCX
Mounting	Magnetic base
Housing color	Black

Environmental data

Operating temperature	–40 ° C to +85 ° C
Storage temperature	–40 ° C to +85 ° C
Humidity	40 % ~ 95 % RH
Vibration	Sine sweep 1 G (0-Peak), 10–150–10 Hz each axis

CE approval

Applicable ETSI EN 301 489-19 standards

Product variants

ANN-MS-0-005-0	Active GPS antenna with SMA connector
ANN-MS-1-005-0	Active GPS antenna with SMB connector
ANN-MS-2-005-0	Active GPS antenna with MCX connector

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com. Copyright © 2019, u-blox AG

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the product data sheet.



