Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions

$$\label{eq:max-ey} \begin{split} \text{Max-Eyth-Straße 1} & \cdot \text{74638 Waldenburg} \cdot \text{Germany} \\ \text{Tel.} & +49 \text{ (0)} \text{ 79} \text{ 42} \text{ 945-0} \cdot \text{Fax} & +49 \text{ (0)} \text{ 79} \text{ 42} \text{ 945-400} \\ \text{eiSos@we-online.de} & \cdot \text{www.we-online.de} \end{split}$$



Product / Process Change Notification (PCN) ☐ Major change ☐ Minor change						
PCN #:	PCN_ConMM_20210818	Change Category:				
Affected Series:	WE-ConMM- 690xxxxxxx7x	☐ Equipment / Location☒ General Data☐ Material				
PCN Date:	May 04, 2021	☐ Process				
Effective Date:	August 18, 2021	□ Product Design□ Shipping / Packaging□ Supplier□ Software				
Contact:	Product Management	Data Sheet Change:				
Phone:	+49 (0) 7942 - 945 5001	⊠ Yes □ No				
Fax:	+49 (0) 7942 - 945 5179	Attachment:				
E-Mail:	pcn.eican@we-online.com	□ Yes ⊠ No				

DESCRIPTION AND PURPOSE OF CHANGE:

As a datasheet information amendment, Würth Elektronik will update Working voltage parameter for ConMM according to UL testing

This is a datasheet correction only. There will be no change in form, fit, function, quality or reliability of the product.

DETAIL OF CHANGE:

BEFORE CHANGE

AFTER CHANGE

Electrical Properties:

	Properties		Test conditions	Value	Unit
	Rated Current	I _R	per Pin (PCB)	1.5	Α
	Working Voltage			100	V (AC)
	Withstanding Voltage		1 min	500	V (AC)
	Contact Resistance	R		10	mΩ
	Insulation Resistance	R _{ISO}		1000	ΜΩ

Electrical Properties:

Properties		Test conditions	Value	Unit
Rated Current	I _R	per Pin (PCB)	1.5	Α
Working Voltage			250	V (AC)
Withstanding Voltage		1 min	500	V (AC)
Contact Resistance	R		10	mΩ
Insulation Resistance	R _{ISO}	-	1000	ΜΩ

RELIABILITY / QUALIFICATION SUMMARY:

There will be no change of the product, therefore no additional reliability or qualification testing will be performed.