

High I²t Chip[™] fuse withstands high inrush currents in a 0603 package



CC06H family

Eaton's Bussmann® Series CC06H family features high melting I²t ratings with a solid matrix construction so you can maximize short-circuit performance while avoiding nuisance openings due to inrush currents or cycling conditions.

Extensive offering

The CC06H is the latest offering in the Eaton high-inrush Chip[™] fuse family. The new CC06H family joins an already extensive offering of 0603 and 1206 size chip fuses from Eaton.

Space saving

This compact SMD Chip fuse offers a significant space savings over other SMD devices with similar inrush performance.

Environmentally friendly

The full line of CC06H family fuses are lead-free, halogen free and RoHS compliant, and present no disposal issues at end of life.

Applications

- LCD backlight inverters
- Digital cameras
- DVD and media players
- Bluetooth headsets
- Battery packs



Catalog Symbol



Specifications

Technology: Metal film fusible element

Rated voltage: 32 Vdc (1-8 A)

Interrupting rating: 50 A (1-8 A)

Electrical Characteristics:

| Amp Rating | % of Amp Rating | Opening Time |
|---------------|--------------------|-------------------|
| 1-8 A | 100% | 4 hours minimum |
| 1-7 A | 200% | 1-60 seconds |
| 1-8 A | 250% | 5 seconds maximum |

Dimensions and construction- mm/inches



Technical Application Assistance

Call 636-527-1270

E-mail fusetech@eaton.com

Data Sheets: www.eaton.com/electronics

Order samples on-line: https://tools.eatonelectronics.com/request-form

Eaton Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States www.eaton.com/electronics

© 2017 Eaton All Rights Reserved Printed in USA Publication No. 4043 December 2017

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

For more information visit: www.eaton.com/fuses

