

Features

- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings @ 25°C Unless Otherwise Specified

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 150°C/W Junction to Ambient

Parameter	Symbol	Rating	Unit
Collector-Base Voltage	BF420	300	V
	BF422	250	
Collector-Emitter Voltage	BF420	300	V
	BF422	250	
Emitter-Base Voltage	V_{EBO}	5	V
Continuous Collector Current	I_C	0.1	A
Power Dissipation	P_D	830	mW

**NPN Silicon
Plastic-Encapsulate
Transistor**


TO-92

1.EMITTER
2.COLLECTOR
3.BASE

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.169	0.185	4.30	4.70	
B	0.169	0.185	4.30	4.70	
C	0.500	-----	12.70	-----	
D	0.015	0.022	0.38	0.55	
E	0.130	0.146	3.30	3.70	
G	0.095	0.105	2.42	2.67	Straight Lead
	0.173	0.220	4.40	5.60	Bent

Marking: Type Number

Internal Structure



1.EMITTER
2.COLLECTOR
3.BASE

Electrical Characteristics @ $T_A=25^\circ\text{C}$ Unless Otherwise Specified

Parameter		Symbol	Min	Typ	Max	Units	Conditions
Collector-Base Breakdown Voltage	BF420	$V_{(BR)CBO}$	300			V	$I_C=100\mu\text{A}, I_E=0$
	BF422		250				
Collector-Emitter Breakdown Voltage	BF420	$V_{(BR)CEO}$	300			V	$I_C=1\text{mA}, I_B=0$
	BF422		250				
Emitter-Base Breakdown Voltage		$V_{(BR)EBO}$	5			V	$I_E=100\mu\text{A}, I_C=0$
Collector Cutoff Current		I_{CBO}			0.01	μA	$V_{CB}=200\text{V}, I_E=0$
Emitter Cutoff Current		I_{EBO}			0.05	μA	$V_{EB}=5\text{V}, I_C=0$
DC Current Gain		h_{FE}	50				$V_{CE}=20\text{V}, I_C=25\text{mA}$
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$			0.6	V	$I_C=30\text{mA}, I_B=5\text{mA}$
Transition Frequency		f_T	60			MHz	$V_{CE}=10\text{V}, I_C=10\text{mA}, f=100\text{MHz}$

Ordering Information

Device	Packing
Part Number-AP	Ammo Packing: 20Kpcs/Carton
Part Number-BP	Bulk: 100Kpcs/Carton

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.