



NOTES:

1. SHIPPED ASSEMBLED.
2. $\varnothing 0.04$ [1.0mm] X 0.06 [1.5mm] DEEP HOLE IN PIN FOR SOLDERING.
3. MATERIALS:
HOUSING AND LOCKRING - ZINC ALLOY, NICKEL PLATED
FLEX RELIEF - THERMOPLASTIC, BLACK
INSERT - THERMOPLASTIC, BLACK
PINS - COPPER ALLOY, TIN PLATED
CABLE CLAMP - STEEL, NICKEL PLATED
SCREW - STEEL, NICKEL PLATED
4. THESE PRODUCTS ARE RoHS COMPLIANT.

CUSTOMER DRAWING

REV	ECO NUMBER	DATE	BY	APVD
A	26000	3/3/06	TJK	TJK
REVISIONS				

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES
- TWO PLACE DECIMALS ± 0.02
- THREE PLACE DECIMALS ± 0.005

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE	WIDTH	MULT	LBS/M	TEMPER					
FINISH					MATERIAL				
SPEC No.					SPEC No.				
FIRST USED ON					SCALE				
					3:2				
DATE DRAWN	BY	CHKD	APVD						
24-May-13	TO	TO	TJK						
			5-28-13	2-29-13					
NAME MALE DIN 3-8 PIN LOCKING CORD PLUG CONNECTOR, RoHS									
PART No. 05CL_MX, 09CL_MX, 12CL_MX, 15CL_MX SERIES								REV	A