Product data sheet Characteristics

9001KS62FB

Harmony 9001K, selector switch head, metal, long handle, black, 30mm, 3 positions, spring return left to center





Main

Mairi	
Range of Product	Harmony 9001K
Product or Component Type	Head for selector switch
Device short name	9001KS
Type of operator	Left to centre spring return
Operator profile	Black gloved hand knob

Complementary

Complementary		
Bezel material	Metal	
Mounting diameter	1.18 in (30 mm)	
Net Weight	0.54 lb(US) (0.245 kg)	
Shape of signaling unit head	Round	
Operator position information	3 positions	
Contacts type and composition	Without contact block	
Mechanical durability	500000 cycles	
Device presentation	Basic element	

Environment

Environment	
Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Overvoltage category	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6
Standards	EN/IEC 60947-5-1 JIS C 852 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-4 JIS C 4520 CSA C22.2 No 14
Product Certifications	UL 508 NEMA
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	785901959199	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.00 oz (226.796 g)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	7.62 in (19.355 cm)	
Package 1 width	3.00 in (7.62 cm)	
Package 1 Length	19.35 in (49.161 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	[☑] Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months	