SIEMENS

Data sheet

6GK5721-1FC00-0AB0

product type designation



W721-1 RJ45 (USA)

IWLAN client, SCALANCE W721-1, RJ45, 1 radio, 1 R-SMA antenna port, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM, German/English, 1x joint block; only for operation in the USA.

transfer rate	
transfer rate	
with WLAN / maximum	150 Mbit/s
for Industrial Ethernet	10, 100 Mbit/s
transfer rate / for Industrial Ethernet	
• minimum	10 Mbit/s
maximum	100 Mbit/s
interfaces	
number of electrical connections	
 for network components or terminal equipment 	1
for power supply	1
 for redundant voltage supply 	0
type of electrical connection	
 for network components or terminal equipment 	RJ45 socket
for power supply	3-pole screw terminal
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No
memory	
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No
interfaces / wireless	
number of radio cards / permanently installed	1
number of electrical connections / for external antenna(s)	1
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
consumed current	
at DC / at 24 V / typical	0.15 A
power loss [W]	
at DC / at 24 V / typical	3.6 W
supply voltage / 1	
from terminal block	19.2 V
supply voltage / 2	
 from terminal block 	28.8 V

ambient conditions	
ambient temperature	
during operation	0 55 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20
design, dimensions and weights	
width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	
S7-300 rail mounting	No
S7-1500 rail mounting	No
35 mm top hat DIN rail mounting	Yes
wall mounting	No
radio frequencies	110
operating frequency	2.44 2.40 CHz dononding on the country arrange
• for WLAN in 2.4 GHz frequency band	2.41 2.48 GHz; depending on the country approvals
for WLAN in 5 GHz frequency band	4.9 5.8 GHz; depending on the country approvals
product features, product functions, product components	
product function / Access Point Mode	No
product function / client Mode	Yes
product function	
• iPCF client	No
• iPCF-MC client	No No
product function / iREF	No
product function / iPRP	No
product functions / management, configuration, engineeri	ng
number of manageable IP addresses / in client	4
product function	
• CLI	Yes
web-based management	Yes
MIB support	Yes
TRAPs via email	Yes
• configuration with STEP 7	Yes
configuration with STEP 7 in the TIA Portal	Yes
• WDS	No
protocol / is supported	
Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	
• LLDP	Yes
	No
identification & maintenance function	Voc
I&M0 - device-specific information I&M4 - higher level designation (see that designation)	Yes
I&M1 – higher level designation/location designation	Yes
product functions / diagnostics	

product function	
PROFINET IO diagnosis	No
• link check	No
• connection monitoring IP-Alive	No V
• SysLog	Yes
protocol / is supported • SNMP v1	Voc
• SNMP v2	Yes Yes
SNMP v3	Yes
	Tes
product functions / VLAN	
product function • function VLAN with IWLAN	No
product functions / DHCP	110
product function	
DHCP client	Yes
DHCP server	Yes
DHCP Option 82	Yes
product functions / redundancy	
protocol / is supported	
STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
product functions / security	
product function	
ACL - MAC-based	Yes
 management security, ACL-IP based 	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	Yes
 access protection according to IEEE802.11i 	Yes
WPA/WPA2	Yes
• TKIP/AES	Yes
protocol / is supported	
• SSH	Yes
• RADIUS	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
SIMATIC time synchronization (SIMATIC Time)	Yes
standards, specifications, approvals	
standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
certificate of suitability	
EC Declaration of Conformity	Yes
• CE marking	Yes
• C-Tick	Yes
• E1 approval	No
• railway application in accordance with EN 50155	No
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
 Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	No
Power-over-Ethernet according to IEEE802.3at for type 2	No
standard for wireless communication	N.
● IEEE 802.11a	Yes

• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
● IEEE 802.11i	Yes
● IEEE 802.11n	Yes
wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
standards, specifications, approvals / marine classification	n
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	No
 French marine classification society (BV) 	No
DNV GL	No
 Korean Register of Shipping (KRS) 	No
Lloyds Register of Shipping (LRS)	No
Nippon Kaiji Kyokai (NK)	No
Polski Rejestr Statkow (PRS)	No
Royal Institution of Naval Architects (RINA)	No
standards, specifications, approvals / hazardous environn	nents
standard / for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07
Startdard 7 for Flazardodo 20110	ATEX 0145X
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
accessories	
accessories	24 V DC screw terminal included in scope of delivery
further information / internet-Links	
further information / internet-Links Internet-Link	
Internet-Link • to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool
Internet-Link	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com
Internet-Link to website: TIA Selection Tool to web page: selection aid TIA Selection Tool to the website: IWLAN to website: Industry Mall to website: Information and Download Center	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
Internet-Link • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support	http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax