

ARS-7235-AC Series

Industrial Dual Radio IEEE 802.11a/b/g/n/ac Wireless Access Point/Client/Bridge/Repeater/Router



Features


- ▶ Industrial 2x2 MIMO
- ▶ Qualcomm IPQ4029 SoC
- ▶ Supports IEEE 802.11a/b/g/n/ac
- ▶ Supports 2*10/100/1000 Base-TX WAN/LAN Ports
- ▶ Tx Power 25dB for 2.4GHz
- ▶ Tx Power 24dB for 5GHz
- ▶ WPA, WPA2, WPA3, WEP, TKIP, AES
- ▶ Power Input: 9~48VDC in 6-Pin Terminal Block
- ▶ Reverse Polarity Protection
- ▶ IP30 Protection
- ▶ DIN-Rail and Wall Mountable
- ▶ Operating Temperature Range: STD: -10°C to 60°C; EOT: -35°C to 70°C
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' ARS-7235-AC series is an industrial dual radio IEEE 802.11a/b/g/n/ac wireless LAN access point with added router capabilities. Embedded with the Qualcomm IPQ4029 SoC chipset, it boasts network robustness, stability, and a wide network coverage with a very low voltage input of 9V. Based on IEEE 802.11 a/b/g/n/ac, the access point supports high-speed data transmission of up to 867Mbps.

The ARS-7235-AC series is capable of operating in different modes, which makes it suitable for a wide variety of wireless applications including long-distance deployments. The unit also allows the user to position the wireless antennas in a better signal-broadcasting location for improved wireless coverage and signal strength or simply in a more convenient location.

DIMENSIONS



SPECIFICATIONS

Technology		Power Requirement	
Standards	IEEE 802.11a/b/g/n/ac Wireless LAN	Input Voltage	9–48VDC Redundant Input
	IEEE 802.3 10Base-T Ethernet	Power Connection	1 removable 6-contact terminal block
	IEEE 802.3u 100Base-TX Fast Ethernet	Reverse Polarity Protection	Present
Protocol	IEEE 802.3ab 1000Base-T Gigabit Ethernet	Overload Current Protection	Present
	IP, TCP, UDP, ARP, BOOTP, ICMP, HTTP, HTTPS, DNS Proxy, NTP, Dynamic DNS, SMTP, SNMP	System Power Consumption	3.5 Watts
WLAN Operation Mode	AP/Client/Bridge/Repeater/Router	Environmental Limits	
Encryption Security	WPA, WPA2, WPA3, WEP, TKIP, AES, RADIUS, 802.1x/EAP	Operating Temperature	STD: -10°C to 60°C EOT: -35°C to 70°C
Interface		Storage Temperature	-40°C to 80°C
Ethernet Port	2*10/100/1000Tx	Ambient Relative Humidity	5 to 90%, (non-condensing)
WLAN	Dual Band 2.4GHz/5GHz concurrent	Regulatory Approvals	
Antenna	2*External SMA Antennas:	EMI	FCC Part 15 Subpart B CE EN55032
	3dBi for 2.4GHz, 5dBi for 5GHz (MIMO support, Dual 2Tx/2Rx)	EMS	CE EN55024 IEC61000-4-2,3,4,5,6,8,11
LED Indicators	Power, Fault, Wi-Fi Signal, Link, Activity	Free Fall	IEC60068-2-32
Frequency Range		Shock	IEC60068-2-27
IEEE 802.11a/b/g/n/ac (2.4GHz)	2.402G-2.482GHz, 25dBm	Vibration	IEC60068-2-6
IEEE 802.11a/b/g/n/ac (5GHz)	4.92G-5.92GHz, 24dBm	Green	RoHS Compliant
Mechanical Characteristics		Certifications	FCC, CE
Housing	Metal, IP30 rated	Warranty	5 Years
Dimensions	30 x 140 x 95 mm (W x H x D)		
Weight	Unit: 0.60 lb. Shipping: 1.0 lb.		
Mounting	DIN-Rail mounting, Wall mounting		

ORDERING INFO

ARS-7235-AC	Industrial Dual Radio IEEE 802.11a/b/g/n/ac Wireless Access Point/Client/Bridge/Repeater/Router
ARS-7235-AC-T	Industrial Dual Radio IEEE 802.11a/b/g/n/ac Wireless Access Point/Client/Bridge/Repeater/Router; EOT: -35°C to 70°C