

**Product Summary** (@T<sub>A</sub> = +25°C)

V <sub>RRM</sub> (V)	I <sub>O</sub> MAX (A)	V <sub>F</sub> MAX (V)	I <sub>R</sub> MAX (μA)
400, 600, 800, 1000	3	1.1	5

**Description and Applications**

Suitable for AC to DC bridge full wave rectification for AC/DC Power Supply, LED lighting, home appliances, office equipment, and telecommunication applications.

**Features and Benefits**

- Glass Passivated Die Construction
- High Case Dielectric Strength of 1000 PRV
- Low Reverse Leakage Current
- Surge Overload Rating to 90A Peak
- Ideal for Printed Circuit Board Applications
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**

**Mechanical Data**


- Case: KBP
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish – Tin. Plated Leads, Solderable per MIL-STD-202, Method 208
- Polarity: Marked on Body
- Weight: 1.52 grams (Approximate)

**KBP**

**Ordering Information** (Note 3)

Part Number	Compliance	Case	Packaging
KBP304G	Commercial	KBP	35 Pieces per Tube
KBP306G	Commercial	KBP	35 Pieces per Tube
KBP308G	Commercial	KBP	35 Pieces per Tube
KBP310G	Commercial	KBP	35 Pieces per Tube

- Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
  2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.

**Marking Information**


**Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Characteristic	Symbol	KBP304G	KBP306G	KBP308G	KBP310G	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	400	600	800	1000	V
Working Peak Reverse Voltage	V <sub>RWM</sub>					
DC Blocking Voltage	V <sub>RM</sub>					
RMS Reverse Voltage	V <sub>R(RMS)</sub>	280	420	560	700	V
Average Rectified Output Current (With Heatsink)	I <sub>O</sub>	3.0				A
@T <sub>C</sub> = +105°C (Without Heatsink)		1.9				
Non-Repetitive Peak Forward Surge Current @T <sub>J</sub> = +25°C	I <sub>FSM</sub>	90				A
8.3ms Single Half Sine-Wave Superimposed on Rated Load @T <sub>J</sub> = +125°C		80				
Non-Repetitive Peak Forward Surge Current @T <sub>J</sub> = +25°C	I <sub>FSM</sub>	180				A
1.0ms Single Half Sine-Wave Superimposed on Rated Load @T <sub>J</sub> = +125°C		160				
I <sup>2</sup> t Rating for Fusing (3ms ≤ t ≤ 8.3ms)	I <sup>2</sup> t	26.5				A <sup>2</sup> s

**Thermal Characteristics**

Characteristic	Symbol	Value	Unit
Typical Thermal Resistance, Junction to Case (Note 4)	R <sub>θJC</sub>	10	°C/W
Typical Thermal Resistance, Junction to Lead (Note 4)	R <sub>θJL</sub>	12	°C/W
Typical Thermal Resistance, Junction to Ambient (Note 4)	R <sub>θJA</sub>	30	°C/W
Typical Thermal Resistance, Junction to Case (Note 5)	R <sub>θJC</sub>	12	°C/W
Typical Thermal Resistance, Junction to Lead (Note 5)	R <sub>θJL</sub>	18	°C/W
Typical Thermal Resistance, Junction to Ambient (Note 5)	R <sub>θJA</sub>	40	°C/W
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150	°C

**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition	
Reverse Breakdown Voltage (Note 6)	V <sub>(BR)R</sub>	1,000	KBP310G	—	—	V	I <sub>R</sub> = 5μA
		800	KBP308G				
		600	KBP306G				
		400	KBP304G				
Forward Voltage Drop per Element	V <sub>F</sub>	—	0.91	1.1	V	I <sub>F</sub> = 3A, T <sub>J</sub> = +25°C	
Leakage Current (Note 6)	I <sub>R</sub>	—	—	5	μA	V <sub>R</sub> = V <sub>RRM</sub> , T <sub>J</sub> = +25°C V <sub>R</sub> = V <sub>RRM</sub> , T <sub>J</sub> = +125°C	
Total Capacitance per Element	C <sub>T</sub>	—	35	—	pF	V <sub>R</sub> = 4.0V <sub>DC</sub> , f = 1MHz	

Notes: 4. Thermal resistance from junction to case per element. Device mounted on 30mm x 30mm x 1mm Cu Plate Heatsink.  
5. Thermal resistance from junction to case per element without heat sink.  
6. Short duration pulse test used to minimize self-heating effect.




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-repetitive Surge Current




Figure 3. Typical Total Capacitance (Per Element)




Figure 4. Typical Forward Characteristics




Figure 5. Typical Reverse Characteristics





Figure 6. Non-repetitive Surge Current

**Package Outline Dimensions**

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

**KBP**



KBP			
Dim	Min	Max	Typ
A	3.35	3.65	-
A3	0.80	1.10	-
b	0.76	0.86	-
b2	1.22	1.42	-
c	0.35	0.55	-
D	14.25	14.75	-
E	10.20	10.60	-
e	3.56	4.06	-
L	14.25	14.73	-
L1	1.80	2.20	-
z	1.40	1.70	-
a	-	-	3°
a1	-	-	2°
All Dimensions in mm			

NEW PRODUCT

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2018, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)