

HiPerFRED²

V_{RRM} = 400V
 I_{FAV} = 2x 10A
 t_{rr} = 45ns


High Performance Fast Recovery Diode

Low Loss and Soft Recovery


Common Cathode

Part number

DPG20C400PC



Backside: cathode

**Features / Advantages:**

- Planar passivated chips
- Very low leakage current
- Very short recovery time
- Improved thermal behaviour
- Very low I_{rm} -values
- Very soft recovery behaviour
- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low I_{rm} reduces:
 - Power dissipation within the diode
 - Turn-on loss in the commutating switch

Applications:

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode
- Rectifiers in switch mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)

Package: TO-263 (D2Pak)


- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

Fast Diode

Symbol	Definition	Conditions	Ratings			
			min.	typ.	max.	
V_{RSM}	max. non-repetitive reverse blocking voltage	$T_{VJ} = 25^\circ C$			400	V
V_{RRM}	max. repetitive reverse blocking voltage	$T_{VJ} = 25^\circ C$			400	V
I_R	reverse current, drain current	$V_R = 400 V$ $V_R = 400 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 150^\circ C$		1 0.15	μA mA
V_F	forward voltage drop	$I_F = 10 A$ $I_F = 20 A$ $I_F = 10 A$ $I_F = 20 A$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 150^\circ C$		1.32 1.51 1.03 1.24	V V V V
I_{FAV}	average forward current	$T_C = 150^\circ C$ rectangular $d = 0.5$	$T_{VJ} = 175^\circ C$		10	A
V_{F0} r_F	threshold voltage slope resistance } for power loss calculation only		$T_{VJ} = 175^\circ C$		0.77 19.8	V $m\Omega$
R_{thJC}	thermal resistance junction to case				2.3	K/W
R_{thCH}	thermal resistance case to heatsink			0.25		K/W
P_{tot}	total power dissipation		$T_C = 25^\circ C$		65	W
I_{FSM}	max. forward surge current	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}; V_R = 0 V$	$T_{VJ} = 45^\circ C$		150	A
C_J	junction capacitance	$V_R = 200 V$ $f = 1 \text{ MHz}$	$T_{VJ} = 25^\circ C$		12	pF
I_{RM}	max. reverse recovery current		$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		4 6	A A
t_{rr}	reverse recovery time	$I_F = 10 A; V_R = 270 V$ $-di_F/dt = 200 A/\mu s$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		45 65	ns ns

Package TO-263 (D2Pak)			Ratings			
Symbol	Definition	Conditions	min.	typ.	max.	Unit
I_{RMS}	RMS current	per terminal			35	A
T_{VJ}	virtual junction temperature		-55		175	°C
T_{op}	operation temperature		-55		150	°C
T_{stg}	storage temperature		-55		150	°C
Weight				2		g
F_c	mounting force with clip		20		60	N

Product Marking



Part number

D = Diode
 P = HiPerFRED
 G = extreme fast
 20 = Current Rating [A]
 C = Common Cathode
 400 = Reverse Voltage [V]
 PC = TO-263AB (D2Pak) (2)

Ordering	Part Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	DPG20C400PC	DPG20C400PC	Tape & Reel	800	507327

Similar Part	Package	Voltage class
DPG20C400PB	TO-220AB (3)	400
DPG20C400PN	TO-220ABFP (3)	400


Equivalent Circuits for Simulation

* on die level

 $T_{VJ} = 175 \text{ }^{\circ}\text{C}$


I	V_0	R_0	Fast Diode	
$V_{0\max}$	threshold voltage	0.77		V
$R_{0\max}$	slope resistance *	16.6		$\text{m}\Omega$

Outlines TO-263 (D2Pak)



Dim.	Millimeter		Inches	
	min	max	min	max
A	4.06	4.83	0.160	0.190
A1	typ. 0.10		typ. 0.004	
A2	2.41		0.095	
b	0.51	0.99	0.020	0.039
b2	1.14	1.40	0.045	0.055
c	0.40	0.74	0.016	0.029
c2	1.14	1.40	0.045	0.055
D	8.38	9.40	0.330	0.370
D1	8.00	8.89	0.315	0.350
D2	2.5		0.098	
E	9.65	10.41	0.380	0.410
E1	6.22	8.50	0.245	0.335
e	2,54 BSC		0,100 BSC	
e1	4.28		0.169	
H	14.61	15.88	0.575	0.625
L	1.78	2.79	0.070	0.110
L1	1.02	1.68	0.040	0.066
W	typ. 0.02	0.040	typ. 0.0008	0.002

All dimensions conform with
and/or within JEDEC standard.



Fast Diode